EPA Board Policy
Noise limits for wind energy projects

ENVIRONMENT PROTECTION AUTHORITY

Application

This policy is adopted by the Board of the Environment Protection Authority (EPA Board) for the purpose of assessing wind energy projects and requiring conditions or restrictions in respect to wind farm noise under the *Environmental Management and Pollution Control Act 1994* (EMPCA).

This policy supersedes any previous policy of the EPA Board in respect to operational noise criteria for wind energy projects. This policy does not apply to construction noise.

This policy applies from 31 July 2025 and will apply to all wind energy projects currently under assessment. It remains in place until revoked.

Technical terms

L_{Aeq} means the A-weighted equivalent continuous sound level.

L_{A90} means the A-weighted sound level that is exceeded for 90% of the measurement period.

dB means decibel.

dB(A) means decibel when stating A-weighted sound pressure level.

Design Criteria

The predicted equivalent noise level at any noise sensitive premises should not exceed the greater of:

a) **35 dB(A) $L_{Aeq,\ 10\ min}$; or**
b) **Background (L_{A90}) + 5 dB(A).**

This design criteria applies to all noise emissions from the activity, inclusive of wind turbines and all ancillary infrastructure. It has been set for the protection of sensitive receivers during periods of low background noise.

The background noise for day, evening and night-time must be calculated separately to determine the applicable (lowest) background level, and is not to be averaged across a 24-hour period.

For predictive purposes, a difference of ~2 dB between measured $L_{A90,\ 10\ min}$ levels and $L_{Aeq,10\ min}$ emissions from the activity must be noted. The predicted noise levels should be adjusted for special audio characteristics and/or the applicable adjustment factors must be discussed.

The EPA South Australia *Wind farms environmental noise guidelines 2021* (or the most recent revised version of that document) is to be used for assessing whether a wind farm can meet this design criteria, except where that guideline may be inconsistent with this policy.

Noise Measurements

If approved, wind energy projects will contain conditions and restrictions to enforce the design criteria. The following guidance is provided for the interpretation of EPA Board wind energy project noise requirements:

1. It is generally acceptable for wind turbine noise to be measured in L_{A90}, but note that alternative techniques may be required (including measuring in L_{Aeq}) to better detect special audible characteristics (dominant and intrusive characteristics) and noise fluctuations or intermittent noise.

2. An appropriate conversion factor must be added to the measured L_{A90} level to derive the representative L_{Aeq} noise level. To be representative of L_{Aeq}, generally applying +2 dB(A) conversion factor to the measured L_{A90} level is acceptable.

3. Where special audible characteristics (dominant and intrusive characteristics) are detected from any wind farm noise, a correction factor must be applied in accordance with the *Tasmanian Noise Measurement Procedures Manual*.

4. The EPA South Australia *Wind farms environmental noise guidelines 2021* (or the most recent revised version of that document) is to be used for all wind farm noise measurements, except where that guideline may be inconsistent with this policy.

29 July 2025



Andrew Paul
Chair
Environment Protection Authority Board